


UV Hybrid Series



Side view



Basic Features

Type	Hybrid series
Print Head	SG1024(10PL)
Print head control	Automatic PH Temp. and voltage Adjustment
Feed system	Automatic rotary motor achieves optimal tension of media
Take-up system	Automatic rotary motor
Printing method	Roll to roll/sheet to sheet
Ink	UV Ink
Ink tank	Continuous ink supply/Capacity 1500ML
Curing	Mercury UV lamp
RIP software	photoprint/ONYX/Caldera
Color management	ICC Based Color, Curves Adjustment, Density Adjustment
File Format	TIFF,JPEG,Postscript,EPS and PDF
Power supply	16A/380V
Operation	Temperature : 20°C-28°C
Environment	Related humidity : 40% - 70%

Technical Specification

Media width	3.3m
Printing width	3.2m
Media thickness	0-60mm
PH numbers	4/6/7/8
Resolution	600dpix800dpi~600dpix1600dpi
Printing speed	4pass 56m ² /h 12pass 20m ² /h 6pass 38m ² /h 16pass 16m ² /h 8pass 30m ² /h
Colors	4 colors(C M Y K) or 6 colors(C M Y K Lc Lm). White & varnish can be optional
Media Types	Corrugated board, Foam board, PVC, Tile, Glass Acrylic, Wood, Metal, Paper, Banner, Wall paper Leather, Mesh, Self-adhesive etc.
Outdoor life	2 years (Use GZ Ink)
Dimensions	5.6mx3mx1.7m
Weight	3500kg